



Quick Shine® Multi-Surface Finish and Quick Shine® Hardwood Floor Luster are water-borne polymer formulations designed to protect and impart a rich, deep, protective glow to sealed hardwood floors, wood laminate, stone, tile, vinyl and all other sealed hard surface flooring.

#### **FINISH IT**

- Dry dust mop prior to applying Quick Shine® Multi-Surface Finish or Hardwood Luster Finish to remove any dust/debris from your floors. For light cleaning, you can clean your floor with our white microfiber bonnet, a sponge mop, or microfiber applicator dampened with plain, cool tap water
- After floor is free of debris, pet hair and dust, squirt Finish in an S-shape onto floor in small 5 foot x 5 foot sections at a time.
- Quickly spread the finish with our Quick Shine® Hardwood Floor Mop using broad, even strokes with a slightly dampened microfiber mop pad.
- Dries to a gloss in 30 minutes.
- After floor is completely dry additional coats can be applied using the same method as above if a higher gloss is desired. Allow the 1st coat to dry for one hour before applying additional coats.

#### **MAINTAIN IT**

- Keep the finish glow fresh by dry dusting weekly with a dry microfiber mop such as our Quick Shine® Hardwood Floor Mop in order to eliminate everyday dust and debris.
- For small spills, paw prints, or foot prints clean with our Quick Shine® Daily Care spray cleaners. Simply mist area and wipe clean with a damp microfiber cloth.
- For a large area, or to clean heavier dirt or soil use our Quick Shine® Cleaners in our Quick Shine® Spray Mop for quick and easy cleaning. The squirt-top cleaners can also be used directly on the floor. It is important to rinse and wring the pad frequently in order to release the dirt from the pad to prevent streaking and hazing.

#### **REFRESH IT**

- Every 2-4 months reapply a fresh new coat of Quick Shine® Multi-Surface Floor Finish or Hardwood Floor Luster to enhance the glow. Remove all debris, pet hair and dust before applying.
- Each time you refresh repeat the "Maintain It" bullet points above for maximum gloss protection. If you have unevenly worn hardwood floors, simply add an extra coat to these areas. Uneven seals can occur where certain high traffic areas of the floor lose their polyurethane seal due to wear and tear. Either product is a great stop-gap method to forego a complete sanding and refinishing. We have had many consumers tell us these products have transformed their unevenly worn seal or completely unsealed hardwood floors.

#### **PREVENT IT**

- Establish floor mats or throw rugs at entryways and walkways to minimize the abrasion of the finish caused by dirt and grit tracking.
- Place felt-tipped protectors on bottoms of chair and furniture legs.
- Keep pet nails trimmed.
- Try going shoe-less as barefoot/sock traffic is better than shoe traffic.